

126 Capital Court Nicholasville KY. 40356
1-866-931-4363 scott@idealproductsinc.net



2033G Green Laser Sight for PAN



Standard over the barrel mount

Specs:

Output power	Certified	4.0~ 5.0 mw
Wavelength		532nm
Beam mode		TEM ₀₀
Beam dia.		< 1.5 mm at aperture
Beam divergence		<1.2mrad
Optimum operating temp		20c - 30c
Operating current		<300ma
Input voltage		3V
Safety class		FDA IIIa, IEC 3R

K2033G Full Kit



Assembly: This laser comes pre-sighted. The battery is removed for shipping. Unscrew the mounting sleeve counter clockwise. The standard CR123, 3 volt battery is inserted with the positive end towards the over the barrel or bore type mount. This mount can be exchanged for the over the barrel, smooth bore adapter, or the rifle bore adapter. **After each adapter is changed, the laser must be re-sighted.**

Sighting: Locate the windage and elevation screws. Use the .062 Allen wrench to adjust the screws. End in a clockwise direction. **Do not remove Warning label.**

Care: Keep o-rings clean and free of debris. The white o-rings can be removed and cleaned with soap and water. O-rings can become tighter when not used for long periods of time. Put adapter on barrel for a few minutes and then remove. This will stretch the o-ring. Lubrication can be used. Keep in mind, lubricants will attract dirt.

2033B



Bore Mount for Smooth Tip

2033R



Bore Mount for Rifle Tip