

Ideal Products, Inc. 126 Capital Ct. Nicholasville, KY40356 Toll Free: 1-866-931-4EOD

RD 24 Disrupter



- •24 inch long disrupter
- •Rifling (1 revolution in 35 inches)
- •Made of Stainless Steel (proprietary grade) heat treated to RC 32
- •Barrel is 1.125 diameter at tip to accept standard PAN laser sight and accessories
- •Breech end is 1.5 inches in diameter with 1.5 inches x 6 acme threads. Threads are made to match standard T3 Disrupter Breech, Electric Breech and EBW Breech (made by Ideal Products, Inc.). All T3 disrupter breeches will fit RD24 barrel
- •RD24 barrel has a Picatinny rail mounted in front of breech to accept accessories
- •Barrel has a standard 3.5 chamber to accept standard 12 gauge PAN ammo and new sabot rounds designed to fit PAN (ammo manufactured by L-Tech Enterprises, Inc.)
- •Weighs 7.3 pounds with rail (without breech)
- •1-1/2 inch diameter clamping surface allows the RD24 to mount in standard PAN clamps on stands and robots

TheRD24 Disrupter was designed and built as a full 24 inch rifled barrel to allow the user to fire special sabot rounds designed by L-Tech Enterprises, Inc. at targets from longer and safer distances. The Picatinny rail attachment allows the user to mount lights, laser sights, scopes and other rail accessories. As of this date, no other disrupter has the capabilities to fire the special rounds and use the standard T3 Breeches. For specific velocities, accuracy and penetrations of the different rounds available to be used in the RD24 Disrupter, please contact Larry Henderson with L-Tech Enterprises, Inc. His phone number is 606-423-9782