



Ideal Products, Inc.
126 Capital Ct. Nicholasville, KY 40356
Toll Free: 1-866-931-4EOD

“Wildcat” Disrupter

- The Wildcat is a Breech loaded, 12 Gauge system, that can accept up to 3½” fired rounds. Velocities up to 3650 Feet per second for specific rounds.
- The Wildcat is Shock Tube initiated, and percussion actuated. It has a floating firing pin.
- LARGE** Water volume of 140ml to maximize disruption (Velocity of 1450 feet per second).
- It is constructed of high grade Stainless Steel, capable of withstanding chamber pressures of at least 20,000 psi and has been tested using flash testing including Flash X-Ray and Chronographs.
- Two or more targets inside the bomb can be impacted with an isochronicity of 500 microseconds of each other.
- The Wildcat has a 24" Barrel with 1.5 inch ACME threads. This thread will not let the breech lock onto the barrel. It will also reduce loading time. 5 revolutions instead of 16 like the original PAN™.
- The Wildcat Barrel has a section in front of the knurling that is 30mm in diameter. This is for off the shell adapters, like scope rings, picatinny rails and others.



Full kit
 K102 Shown with components
 Case and stand not shown

Qty	Part #	Description
1	1107	24" Stainless Steel Barrel (12ga)
1	4340	ACME Breech Cap
1	K4350PL	Push Lock Breech Plug (assembled)
1	2001	Seating Tool
1	2010	Shell Extractor
1	7250PL	7/16 Nut Driver
1	2045	Gun Bore Cleaning Kit
1	K2001	Laser Sight and Adapter
1	2050	Omni MK31 Initiator
1	2055	Duke Pro (ESI/2) Initiator
1	3130	WD-40
1	7110	Firing Pin Tool

Qty	Part #	Description
2	3000PL	Firing Pins (part # 3000PL)
3	3020PL	Springs (part # 3020PL)
1	4351	Push Lock Fitting
4	3073YPL	Push Lock "Y" Fitting
2	3073CPL	Push Lock Coupling
50	3090	Red Plugs
50	3100	Black Plugs
1	5000	Operator's Manual (CD)
1	K4020	Plastic Case with foam insert
1	K3118	Aluminum Post Stand